Product Cut Sheet

UNIVERSAL EARTHQUAKE BRACING KIT

This adjustable wall/ceiling brace provides a means of securing an equipment rack or auxiliary frame to meet earthquake safety codes.

 Material is 2" x 1/4" steel finished with Gold Chem Film over zinc plating

Kit consists of:

- 4 each brackets (make 2 swivel brackets)
- 2 each 1/2-13 x 1 1/4" hex bolts
- 2 each 1/2-13 hex nuts
- 2 each 1/2" split lock washers

Installation will require (not included):

- 1 each 5/8-11 threaded rod of appropriate length.
 (See P/N 11440.) Rod must be trimmed to proper length during installation
- 2 each 5/8-11 hex nuts
- 2 each 5/8 flat Type A washer, wide
- Clip kit and hardware for attachment to channel or bar

Installation may also require (not included):

For concrete ceiling:

- 1 each 5/8-11 concrete anchor (P/N 06001-001)
- 1 each 5/8-11 x 3" stud (P/N 08001-002)
- 2 each 5/8-11 hex nuts (P/N 20142-111)
- 1 each 5/8" split lock washer (P/N 04003-001)
- 1 each 5/8" flat, washer, wide, Type A (P/N 20283-022)

■ For rack:

- 1 each 5/8-11 x 1 1/4" hex cap screw (P/N 02004-006)
- 1 each 5/8-11 hex nut (P/N 20142-111)
- 1 each 5/8" split lock washer (P/N 04003-001)

■ For auxiliary frame or grid:

- 1 each Grid Clamp Kit (P/N 10609)
- 1 each 5/8-11 x 3 1/4" hex screw cap (P/N 02004-007)
- 1 each 5/8-11 hex nut (P/N 20142-111)
- 1 each 5/8" split lock washer (P/N 04003-001)

For plywood backboard:

- 1 each 5/8" x 2" hex lag screw (P/N 02006-022)
- 1 each 5/8" split lock washer (P/N 04003-001)

NOTE: Seismic installation requirements should be approved by a licensed structural engineer.

Part Number	Description	Shipping Weight
10562-001	Universal Earthquake Bracing Kit	3 lb





