Product Information Sheet COMPRESSION LUGS

Compression Lugs connect copper or tinned copper conductors to busbars, CPI Racks, Cabinets or Cable Runway. Select lugs to match the cable size and mounting hole spacing.

- Available in three styles: Two-Hole, Slotted and 90° Slotted
- Two-Hole Lugs have round holes spaced to match hole spacing on busbars.
- Slotted and 90° Slotted Lugs have one round and one obround hole to match hole spacing on equipment mounting rails on CPI Racks and Cabinets and on some busbars
- Manufactured from electroplated tinned copper
- For use on copper or tinned-copper conductors
- Long barrel allows two or three crimps for secure cable connections
- Lugs have inspection ports to ensure proper cable insertion prior to crimping
- Available individually or in bulk quantities
- Other configurations available
- UL Listed

Slotted Lug

Two-Hole Lug

Part Number	Description	Cable Size	Hole Spacing	Screw Size	Color Code	Qty.	Shipping Weight
40162-901	Two-Hole Lug	#6	.625″	1/4″	Blue	1	1 lb (0.5 kg)
40162-951	Two-Hole Lug	#6	.625″	1/4″	Blue	50	2 lb (0.9 kg)
40162-902	Two-Hole Lug	#6	.75″	3/8"	Blue	1	1 lb (0.5 kg)
40162-952	Two-Hole Lug	#6	.75″	3/8"	Blue	50	2 lb (0.9 kg)
40162-903	Two-Hole Lug	#6	1″	3/8"	Blue	1	1 lb (0.5 kg)
40162-953	Two-Hole Lug	#6	1″	3/8"	Blue	50	2 lb (0.9 kg)
40162-904	Two-Hole Lug	#2	.625″	1/4″	Brown	1	1 lb (0.5 kg)
40162-954	Two-Hole Lug	#2	.625″	1/4″	Brown	25	2 lb (0.9 kg)
40162-905	Two-Hole Lug	#2	.75″	3/8"	Brown	1	1 lb (0.5 kg)
40162-955	Two-Hole Lug	#2	.75″	3/8"	Brown	25	2 lb (0.9 kg)
40162-907	Two-Hole Lug	#2	1″	3/8"	Brown	1	1 lb (0.5 kg)
40162-957	Two-Hole Lug	#2	1″	3/8"	Brown	25	2 lb (0.9 kg)
40162-909	Two-Hole Lug	2/0	1″	3/8"	Black	1	1 lb (0.5 kg)
40162-959	Two-Hole Lug	2/0	1″	3/8"	Black	10	2 lb (0.9 kg)
40162-910	Two-Hole Lug	2/0	1.75″	1/2″	Black	1	1 lb (0.5 kg)
40162-960	Two-Hole Lug	2/0	1.75″	1/2″	Black	10	2 lb (0.9 kg)
40162-911	Two-Hole Lug	4/0	1″	3/8"	Purple	1	1 lb (0.5 kg)
40162-961	Two-Hole Lug	4/0	1″	3/8"	Purple	10	2 lb (0.9 kg)
40162-912	Two-Hole Lug	4/0	1.75″	1/2″	Purple	1	1 lb (0.5 kg)
40162-962	Two-Hole Lug	4/0	1.75″	1/2″	Purple	10	3 lb (1.4 kg)
40162-913	Slotted Lug	#6	.5"/.625"	1/4″	Blue	1	1 lb (0.5 kg)
40162-963	Slotted Lug	#6	.5"/.625"	1/4″	Blue	25	2 lb (0.9 kg)
40162-914	90° Slotted Lug	#6	.5"/.625"	1/4″	Blue	1	1 lb (0.5 kg)
40162-964	90° Slotted Lug	#6	.5"/.625"	1/4″	Blue	25	2 lb (0.9 kg)

Note: Installation hardware not included. Order stainless steel cap screws, lock washers and hex nuts separately.

800-834-4969 in U.S. & Canada • www.chatsworth.com



©2008 Chatsworth Products, Inc. All rights reserved. CPI, Saf-T-Grip, Seismic Frame, SlimFrame and MegaFrame are federally registered trademarks of Chatsworth Products, Inc. CPI Passive Cooling, Cube-iT Plus, Evolution, Simply Efficient, TeraFrame and QuadraRack are trademarks of Chatsworth Products, Inc. All other trademarks belong to their respective companies. 07/08