

MGS400-123

Material ID: 700206691

GigaSPEED® XL MGS400 Series Category 6 U/UTP Information Outlet, yellow



CHARACTERISTICS

Dimensions

| | | | |
|--------|----------|--|---------|
| Depth | 30.48 mm | | 1.20 in |
| Height | 20.32 mm | | 0.80 in |
| Width | 20.32 mm | | 0.80 in |

Electrical Specifications

| | |
|---|--------------------------------|
| ANSI/TIA Category | 6 |
| Contact Resistance Variation, maximum | 20 mOhm |
| Contact Resistance, maximum | 100 mOhm |
| Current Rating | 1.5 A @ 20 °C 1.5 A @ 68 °F |
| Dielectric Withstand Voltage, RMS, conductive surface | 1500 Vac @ 60 Hz |
| Dielectric Withstand Voltage, RMS, contact-to-contact | 1000 Vac @ 60 Hz |
| Insulation Resistance, minimum | 500 MOhm |

Environmental Specifications

| | |
|-----------------------|--------------------------------------|
| Flammability Rating | UL 94 V-0 |
| Operating Temperature | -10 °C to +60 °C (+14 °F to +140 °F) |
| Relative Humidity | Up to 95%, non-condensing |
| Safety Standard | cUL UL |
| Storage Temperature | -40 °C to +70 °C (-40 °F to +158 °F) |

General Specifications

| | |
|-------------------|---------------------------|
| Brand | GigaSPEED® XL SYSTIMAX® |
| Cable Type | U/UTP (unshielded) |
| Color | Yellow |
| Product Type | Outlet |
| Package, quantity | 1 |

Product Specifications

MGS400-123 - Material ID: 700206691

Mechanical Specifications

| | |
|----------------------------------|---|
| Conductor Gauge, solid | 22 AWG 24 AWG 26 AWG |
| Conductor Gauge, stranded | 22 AWG 24 AWG |
| Conductor Type | Solid Stranded (7 strands) |
| Material Type | Copper alloy High -impact, flame retardant, thermoplastic |
| Outlet/Module Contact Plating | Precious metals |
| Plug Insertion Life Test Plug | IEC 60603-7 compliant plug |
| Plug Insertion Life, minimum | 750 times |
| Plug Retention Force, minimum | 30 lbf 133 N |
| Rear Termination Contact Plating | Precious metals |
| Rear Termination Type | IDC |
| Wiring | T568A T568B |

Regulatory Compliance/Certifications

| Agency | Classification |
|-----------------|--|
| RoHS 2002/95/EC | Compliant |
| ISO 9001:2008 | Designed, manufactured and/or distributed under this quality management system |

