

MFC-SCR-09-BG

Material ID: 760007070

Behind The Wall Pre-Radiused SC Connector for 0.9 mm Fiber, multimode



CHARACTERISTICS

Construction Materials

Fiber Type	LazrSPEED® 150, 50 µm multimode fiber LazrSPEED® 300, 50 µm multimode fiber LazrSPEED® 550, 50 µm multimode fiber OptiSPEED®, 62.5 µm multimode fiber
Ferrule Geometry	Pre-radiused
Ferrule Material	Zirconia

Dimensions

Compatible Cable Diameter	0.9 mm 0.0 in
Length	52.0 mm 2.0 in

General Specifications

Interface	SC
Body Style	BTW
Interface Feature	Standard
Color	Beige
Package, quantity	1

Mechanical Specifications

Cable Retention Strength, maximum	0.23 kg @ 0 ° 0.50 lb @ 0 °
-----------------------------------	--------------------------------

Optical Performance

Insertion Loss, typical	0.30 dB
Return Loss, minimum	20.0 dB
Insertion Loss Change, mating	0.30 dB
Insertion Loss Change, temperature	0.30 dB

Optical Specifications

Optical Components Standard	ANSI/TIA-568-C.3
-----------------------------	------------------

Product Specifications

MFC-SCR-09-BG - Material ID: 760007070

Regulatory Compliance/Certifications

Agency

RoHS 2002/95/EC
ISO 9001:2008

Classification

Compliant
Designed, manufactured and/or distributed under this quality management system



* Footnotes

Insertion Loss Change, mating	Maximum insertion loss change after 500 matings
Insertion Loss Change, temperature	Maximum insertion loss change from 0 °C to +60 °C (+32 °F to +140 °F)