

MFC-LCR-09-BG

Material ID: 760034181

Behind The Wall Pre-Radiused LC Connector for 0.9 mm Fiber, multimode



## CHARACTERISTICS

### Construction Materials

Fiber Type	LazrSPEED® 150, 50 µm multimode fiber   LazrSPEED® 300, 50 µm multimode fiber   LazrSPEED® 550, 50 µm multimode fiber   OptiSPEED®, 62.5 µm multimode fiber
Ferrule Geometry	Pre-radiused
Ferrule Material	Zirconia

### Dimensions

Compatible Cable Diameter	0.9 mm   0.0 in
Length	32.0 mm   1.3 in

### General Specifications

Interface	LC
Body Style	BTW
Interface Feature	Standard
Color	Beige
Package, quantity	1

### Mechanical Specifications

Cable Retention Strength, maximum	0.23 kg @ 0 ° 0.50 lb @ 0 °
-----------------------------------	--------------------------------

### Optical Performance

Insertion Loss, typical	0.17 dB
Return Loss, minimum	20.0 dB
Insertion Loss Change, mating	0.30 dB
Insertion Loss Change, temperature	0.30 dB

### Optical Specifications

Optical Components Standard	ANSI/TIA-568-C.3
-----------------------------	------------------

# Product Specifications

MFC-LCR-09-BG - Material ID: 760034181

## Regulatory Compliance/Certifications

---

### Agency

RoHS 2002/95/EC  
ISO 9001:2008

### Classification

Compliant  
Designed, manufactured and/or distributed under this quality management system



## \* Footnotes

---

Insertion Loss Change, mating	Maximum insertion loss change after 500 matings
Insertion Loss Change, temperature	Maximum insertion loss change from 0 °C to +60 °C (+32 °F to +140 °F)