



Middle Atlantic Products, Inc.

www.middleatlantic.com

DRK Series 19" Panel Width Cable Management Enclosure



19" panel width gangable EIA compliant enclosures
Extra wide multi-bay design contains integral cable ducts ideal for accommodating large cable bundles

Features

- One pair of cable ducts with solid steel hinged doors and 4-point magnetic closure pre-installed in front
- 2 pairs of wide 11-gauge rackrail labeled with EIA standard rackspace increments available 10-32 threaded or cage-nut style
- 30" OD width, 31-1/2" and 36" OD depths available
- Fully welded construction provides a 2,500 lb. weight capacity
- 1/8" thick structural steel internal braces
- UL Listed in the US and Canada
- 1/2", 3/4", 1" & 1-1/2" electrical knockouts on rear plates (top & bottom), easily removable for cable pass-through
- Vented rear door
- 4 Grounding and bonding studs installed in base and top
- Durable black textured powder coat finish
- Includes 100 qty. rack screws
- 23" and 24" panel width versions available



DRK19-44-31

Enclosure Accessories
 CONFIGURABLE TOPS
 COOLING FANS
 COPPER BUSS BAR
 CRATING SERVICE
 DOCUMENT POCKET
 DOOR LATCH
 GANGING HARDWARE
 LEVELING FEET
 REMOVABLE SIDE PANELS
 WRINKLE TOUCH-UP PAINT
 for details- see Master Catalog or
 visit www.middleatlantic.com

Architects' and Engineers' Specifications

EIA compliant 19" panel width equipment enclosure shall be Middle Atlantic Products model # DRK19-44-___ (31, 31PRO, 31K, 36, 36PRO). Overall dimensions of enclosure shall be 83-1/2"H x 30"W x ___ (31-1/2", 36")D. Useable height shall be 44 rackspaces, useable depth shall be ___ (24-1/4", 28-3/4"). Fully welded construction shall provide a 2,500 lb. weight capacity. Enclosure shall be constructed of the following materials: top and bottom shall be 14-gauge steel, horizontal braces shall be 1/8" thick steel, all structural elements shall be phosphate pretreated and finished in durable black powder coat. Enclosure shall come equipped with 10" fan top and fan guard for ventilation, one pair of cable ducts with steel doors pre-installed in front of rack, two pairs of 11-gauge steel rackrail with _____ (tapped 10-32, 6mm cage nut) mounting holes in universal EIA spacing, finished in black e-coat with numbered rackspaces, and vented rear door. Grounding and bonding studs shall be zinc plated 1/4-20x1 threaded, installed two each in base and top of enclosure (DRK19-44-31K shall additionally include plexiglass front door, one pair lockable side panels, and leveling feet). Rack shall be UL Listed in the US and Canada.

OPTIONS

- Front doors shall be Middle Atlantic Products model # DPVFD-44 (vented plexi), model # DPF4-44 (plexi), model # DVFD-44 (vented)
- Additional rail kit, 11-gauge, 10-32 threaded, with EIA numbered spacing shall be Middle Atlantic Products model # DRK19-RR44
- Additional rail kit, 11-gauge, cage-nut style, with EIA numbered spacing shall be Middle Atlantic Products model # DRK19-RR44PRO
- Caster base shall be Middle Atlantic Products model # CBS-DRK-31 (31-1/2" overall depth), CBS-DRK-36 (36" overall depth)
- Pair of keylocked side panels shall be Middle Atlantic Products model # SPN-44-312 (31-1/2" overall depth), SPN-44-36 (36" overall depth)
- Optional 10" ventilation fan shall be Middle Atlantic Products model # FAN-10
- Set of four leveling feet shall be Middle Atlantic Products model # LF
- Additional cable duct shall be Middle Atlantic Products model # DRK-44DUCT, sold individually

electronic version available at www.middleatlantic.com

Engineered Mounting Solutions for Low Voltage Applications

US: Riverdale, NJ ■ Simi Valley, CA ■ Harvey, IL ■ Voice: 973-839-1011 Fax: 973-839-1976 ■ www.middleatlantic.com
 Canada: Ottawa, ON ■ Burnaby, BC ■ Voice: 613-836-2501 Fax: 613-836-2690 ■ www.middleatlantic.ca

DRK Series 19" panel width basic dimensions

All dimensions in inches unless otherwise noted

