

Clarity 5E angled 48-port panel, Cat 5e, six-port modules, 19" x 3.5" - OR-PHA5E6U48

Clarity 5E angled 48-port high density patch panel is component compliant to TIA/EIA Category 5e performance requirements. It occupies one rack unit and measures 19" x 3.5". Jacks are grouped in six-port modules. Part of the Clarity 5E link and channel solution that provides significant installed performance headroom.



FEATURES

- **Recessed design with lower mounted profile:** Directs cords more easily to vertical management.
- **ETL verified to TIA Category 5e component spec:** Elevated component performance.
- **Center tuned to Clarity 5E patch cords:** More transparent mated union.
- **Universal wiring:** Supports T568A and T568B installs.
- **Easy lace 110 termination:** Saves installation time.
- **Supplied rear cable management:** Supports good cabling practice.
- **High density design:** Maximizes rack utilization.
- **RoHS compliant:** Lead free.

Specifications

DIMENSION INFO

Height Metric: 88.90 mm

Ortronics

OR-PHA5E6U48

Width Metric: 482.6 mm
Cable Diameter Range: 22-26 AWG
Depth Metric: 46.23 mm
Height U S: 3.5"

GENERAL INFO

Mod Jack Wiring: Universal T568A/B
Number Of Ports: 48

TECHNICAL INFO

Performance Rating: Category 5e
Category Rating: Category 5e

CONSTRUCTION INFO

Component1: Panel - Material1: .090" Aluminum, Finish_Plating1: Painted black texture with green silkscreen
Component4: Array of eight modular dual reactance contacts - Material4: Beryllium copper, Finish_Plating4: Nickel plating and a minimum of 50 micro inches of selective gold plating in contact area
Component5: IDC contacts (low noise) - Material5: Phosphor Bronze, Finish_Plating5: Nickel plating with tin over plate

BUY AMERICAN ACT COMPLIANCE

Country of Origin: MEXICO
Buy American Act Status: Trade Agreement Act Compliant