

Clarity 5E 48-port panel, Cat5e, six-port modules, 19" x 3.5" - OR-PHD5E6U48

Clarity 5E 48-Port High Density Patch Panel is component compliant to EIA/TIA Category 5e performance requirements. It occupies two rack units and measures 19" x 3.5". Jacks are grouped in six-port modules. Part of the Clarity 5E link and channel solution that provides significant installed performance headroom.



FEATURES

- **ETL verified to TIA Category 5e component spec:** Elevated component performance.
- **Center tuned to Clarity 5E patch cords:** More transparent mated union.
- **Universal wiring:** Supports T568A and T568B installs.
- **Easy lace 110 termination:** Saves installation time.
- **Supplied rear cable management:** Supports good cabling practice.
- **High density design:** Maximizes rack utilization.
- **RoHS compliant:** Lead free.

Specifications

DIMENSION INFO

Height Metric: 88.9 mm

Width Metric: 482.6 mm

Ortronics

OR-PHD5E6U48

Cable Diameter Range: 22-26 AWG

Depth Metric: 3.175 mm

Height U S: 3.5 in

GENERAL INFO

Mod Jack Wiring: Universal T568A/B

Number Of Ports: 48

TECHNICAL INFO

Performance Rating: Category 5e

Category Rating: Category 5e

CONSTRUCTION INFO

Component1: Panel - Material1: .094" Aluminum, Finish_Plating1: Painted black texture with green silkscreen

Component4: Array of eight modular dual reactance contacts - Material4: Beryllium copper, Finish_Plating4: Nickel plating and a minimum of 50 micro inches of selective gold plating in contact area

Component5: IDC contacts (low noise) - Material5: Phosphor Bronze, Finish_Plating5: Nickel plating with tin over plate

BUY AMERICAN ACT COMPLIANCE

Country of Origin: MEXICO

Buy American Act Status: Trade Agreement Act Compliant