

## Series II, one-port Clarity 6, T568A/B, 180 degree, Fog White - OR-S21600

Clarity 6 Series II module one jack port (1 unit), ETL verified to TIA Category 6 component specification. Front-loading and front removable. New universal T568A/B wiring label and tapered wiring towers simplify termination. Center tuned to Clarity 6 patch cords for optimum performance. 180°



### FEATURES

- **ETL Verified to Category 6 component standard:** Ensures standards compliance.
- **Center tuned design:** Transparent interface with Clarity 6 cords.
- **Easy lace IDC housing:** Accept larger Cat 6 conductors.
- **Easy to follow T568A and T568B wiring label:** Quick and user-friendly, eliminates confusion.
- **Rugged Series II footprint:** Fits in all Series II faceplates and housings.
- **Front removable:** Less intrusive access for adds, moves, changes.
- **Icon compatible, C6 Marking on jack face:** Supports 606 designation requirements.

### Specifications

#### DIMENSION INFO

Height Metric: 23.37 mm

Width Metric: 48.26 mm

Ortronics

OR-S21600

Depth Metric: 26.42 mm

Height U S: .92"

**GENERAL INFO**

Category Performance Application: Category 6/UTP

Color: Fog White

Footprint: Series II

**TECHNICAL INFO**

Wire Gauge: 22-26 AWG

Category Rating: Category 6

**CONSTRUCTION INFO**

Component2: Array of eight modular dual reactance Category 6 contacts - Material2: Beryllium copper,

Finish\_Plating2: Nickel plating and a minimum of 50 micro inches of selective gold plating in contact area

Component3: IDC contacts (Low noise ) - Material3: Phosphor bronze, Finish\_Plating3: Nickel plating and tin lead over plate

**LISTING AGENCY INFO**

ETL 3027869-003

FCC

UL E131600

**BUY AMERICAN ACT COMPLIANCE**

Country of Origin: MEXICO

Buy American Act Status: Trade Agreement Act Compliant