

Series II, two-port Clarity 5E, T568A/B, 180 degree, fog white - OR-S225E00

Clarity 5E Series II module two jack ports (1 unit), ETL verified to TIA Category 5e component specification. Front-loading and front removable. New universal T568A/B wiring label and tapered wiring towers simplify termination. Center tuned to Clarity 5E patch cords for optimum performance.



FEATURES

- **ETL Verified to Category 5e component standard:** Ensures standards compliance.
- **Center tuned design:** Transparent interface with Clarity 5E cords.
- **Easy lace IDC housing:** Reduces wiring time.
- **Easy to follow T568A and T568B wiring label:** Quick, user-friendly, eliminates confusion.
- **Rugged Series II footprint:** Fits in all Series II faceplates and housings.
- **Front removable:** Less intrusive access for adds, moves, changes.
- **Icon compatible, Category 5e marking on jack face:** Supports 606 designation requirements.

Specifications

DIMENSION INFO

Height Metric: 23.37 mm

Width Metric: 48.26 mm

Ortronics

OR-S225E00

Depth Metric: 30.48 mm

Height U S: .92"

GENERAL INFO

Category Performance Application: Category 5e/UTP

Color: Fog White

Footprint: Series II

TECHNICAL INFO

Wire Gauge: 22-26 AWG

Category Rating: Category 5e

CONSTRUCTION INFO

Component2: Array of eight modular dual reactance contacts - Material2: Beryllium copper, Finish_Plating2: Nickel plating and a minimum of 50 micro inches of selective gold plating in contact area

Component3: IDC contacts (Low noise) - Material3: Phosphor bronze, Finish_Plating3: Nickel plating and tin lead over plate

LISTING AGENCY INFO

ETL 3027869-003

FCC

UL E131600

BUY AMERICAN ACT COMPLIANCE

Country of Origin: MEXICO

Buy American Act Status: Trade Agreement Act Compliant