

Category: Wall and Hard Ceiling - Surface Mount





Many wireless access point manufacturers recommend that the access point be mounted in a horizontal orientation to achieve best wireless coverage. Horizontal mounting may be difficult in hard lid and other environments where the access point is mounted on the wall. Oberon's Model 1009-00 wireless LAN access point wall mount bracket is designed to mount and secure access points from most manufacturers in areas where wall mounting may be required. This aesthetic, white powder coated steel mounting bracket is ideal for mounting the access point in the preferred horizontal orientation in residence halls, hotels, and other hard lid venues. Conduit, raceways, and cable can be terminated in the bracket to provide for a clean appearance. The access point can be locked in place using the access point manufacturer's locking features.

Features

- Conveniently install WAPs on walls and above ceilings
- Designed to enable wireless access points to be mounted in preferred horizontal orientation
- T-bar bracket accommodates access points from most vendors
- Can be mounted directly over telecommunications outlet



Measurements

(maximum values; additional information may be available in Specifications):

Height: 3.00 in. Width: 7.00 in. Depth: 9.00 in. Item Weight: 2.5 lbs. Shipping Weight: 3 lbs.

Specifications

- Textured white powder coated steel construction
- Size: 9" deep x 7" wide x 3" tall
- Shipping weight: approximately 3 lbs

Includes

- (1) Right Angle Bracket
- (1) Installation Instructions

Documentation Links

Installation Instructions - http://oberonwireless.com/images/WebDocs/Model1009-00_Installation_Instructions.pdf

Scustomer Prints - http://oberonwireless.com/images/WebDocs/Model1009-00_Customer_Print.pdf