

**DYMO**®

practically genius

Accu-Tech®  
We're Known by the Companies We Keep

# DYMO Industrial Labels

Label it fast, label it once, label it right.



# Tough, jobsite-tested labels for industrial applications.

Labels

## Rely on DYMO® Industrial Labels.

DYMO Industrial labels are tough – jobsite tested and UL recognized. Thermal transfer printing means labels won't smudge, smear or fade. Choose up to a one-inch label width in a broad assortment of materials and colors that meet OSHA, ANSI, and ISO standards. All DYMO Industrial labels are distributed from an easy-to-load cartridge, and with a split-back design, peeling and applying is quick and easy.

DYMO Industrial labels help you get labeling jobs done fast, and done right – the first time.



DYMO Industrial Labels are available in:

Flexible Nylon  
Permanent Polyester  
Indoor/Outdoor Vinyl  
Heat-Shrink Tube  
Non-Adhesive Tag  
Self-Laminating


## DYMO Industrial Label benefits:

- 1 Industrial-strength adhesives resist moisture, extreme temperatures, UV light and more – so labels won't curl or fall off
- 2 Available in a range of UL recognized materials for virtually every industrial labeling application; heat-shrink tubes tested to SAE, ASTM and military specifications
- 3 Thermal transfer printing technology – label text won't smudge, smear, or fade
- 4 Choose from 1/4", 3/8", 1/2", 3/4" and 1" label widths in a broad color assortment that meet OSHA, ANSI, and ISO standards
- 5 Easy-to-peel split back design makes applying labels quick and easy



IND

# The right label for virtually every situation and surface.



## Indoor/Outdoor Vinyl

For general labeling or extreme conditions. Vinyl labels offer moisture, chemical and UV resistance, making them ideal for labeling both indoors and outdoors. Available in the widest range of colors that adhere to OSHA, ANSI and ISO color standards.

UL recognized as a component to UL 969

## Flexible Nylon

For labeling wires, cables and rounded surfaces. Flexible Nylon labels conform and stick tightly to wires, cables, curved and textured surfaces. Tear-proof material resists damage when pulled through tight spaces or conduits.

UL recognized as a component to UL 969

## Permanent Polyester

For labeling panels, blocks, faceplates, shelves, bins, beams and more. Permanent Polyester labels have a polished finish that leaves your work looking professional. Available in smaller widths that fit most patch panels, blocks and other distribution panels.

UL recognized as a component to UL 969

## Heat-Shrink Tube

For high-end cable identification. A 3:1 shrink ratio helps ensure a secure fit on wires and cables. Print directly on Heat-Shrink Tubes with any DYMO Industrial labeling tool.

Meets MIL-M-81531, MIL-STD-202G, SAE-DTL- 23053/5 (Class 1 & 3)

UL recognized as a component to UL 224

## Non-Adhesive Tag

For sliding into racks or faceplates that do not require adhesive. Made from polyester for increased durability.

## Self-Laminating











Self-Laminating labels protect your printed area from exposure to oil, solvents, water and abrasion when applied to wires and cables.

All DYMO Industrial labels are RoHS compliant.

For technical specifications on all DYMO Industrial label types, please visit our website at:


[www.dymo.com/industrial](http://www.dymo.com/industrial)













## How to choose the right DYMO® Industrial label:

ENVIRONMENT							
SURFACE		Heat/Cold Resistant	UV Light Resistant	Oil Resistant	Water Resistant	Chemical Resistant	Color Coding
	Cable/Wire	Flexible Nylon Heat-Shrink Tube	Indoor/Outdoor Vinyl Heat-Shrink Tube	Indoor/Outdoor Vinyl Heat-Shrink Tube	Indoor/Outdoor Vinyl Heat-Shrink Tube	Indoor/Outdoor Vinyl Heat-Shrink Tube	Indoor/Outdoor Vinyl
	Curved Surface	Flexible Nylon Indoor/Outdoor Vinyl	Indoor/Outdoor Vinyl Flexible Nylon	Indoor/Outdoor Vinyl	Indoor/Outdoor Vinyl Flexible Nylon	Indoor/Outdoor Vinyl	Indoor/Outdoor Vinyl
	Flat Surface	Permanent Polyester Flexible Nylon	Permanent Polyester Indoor/Outdoor Vinyl	Permanent Polyester Indoor/Outdoor Vinyl	Permanent Polyester Indoor/Outdoor Vinyl	Permanent Polyester Indoor/Outdoor Vinyl	Indoor/Outdoor Vinyl
	Textured Surface	Permanent Polyester Flexible Nylon	Indoor/Outdoor Vinyl Permanent Polyester	Indoor/Outdoor Vinyl Permanent Polyester	Indoor/Outdoor Vinyl Permanent Polyester	Indoor/Outdoor Vinyl Permanent Polyester	Indoor/Outdoor Vinyl

Top = Best Option    Bottom = Alternate Option

# Available DYMO® Industrial label widths and colors:



IND		LABEL APPLICATIONS	LABEL COLOR	1/4" 6 mm	3/8" 9 mm	1/2" 12 mm	3/4" 19 mm	1" 24 mm
<b>Labels that stick and stay stuck.</b>  DYMO Industrial labels are tough— jobsite tested and UL recognized. Labels won't smear or fade and are built with industrial-strength adhesives to resist moisture, UV light and extreme temperatures. Whether you are labeling to OSHA, ISO and ANSI color standards or labeling in harsh conditions, DYMO Industrial labels have you covered. DYMO Industrial labels are designed to work exclusively with Rhino™ printers and to perform on a variety of surfaces.  <b>LEARN MORE:</b> <a href="http://www.dymo.com/industrial">www.dymo.com/industrial</a>			BLACK ON WHITE	–	18443	18444	18445	1805430
			BLACK ON YELLOW	–	–	18432	18433	1805431
			BLACK ON ORANGE	–	–	18435	18436	1805427
			BLACK ON GREY	–	–	1805413	1805419	1805425
			WHITE ON RED	–	–	1805416	1805422	1805429
			WHITE ON BLACK	–	1805437	1805435	1805436	1805432
			WHITE ON GREEN	–	–	1805414	1805420	1805426
<b>VINYL</b>  Length 18'   5.5 m  - UL Recognized Component to UL969 - RoHS compliant  			WHITE ON BLUE	–	–	1805243	1805417	1805423
			WHITE ON PURPLE	–	–	1805415	1805421	1805428
			WHITE ON BROWN	–	–	1805412	1805418	1805424
			<b>PERMANENT POLYESTER</b>  Length 18'   5.5 m  - UL Recognized Component to UL969 - RoHS compliant  			BLACK ON WHITE	1805442	18482
BLACK ON CLEAR	1805440	18508DMO				622289	622290	1805433
BLACK ON METALLIC	1805441	18485				18486	18487	1805434
<b>HEAT-SHRINK TUBE</b>  Length 5'   1.5 m  - UL Recognized Component to UL224 - Meets MIL-STD-202G, MIL-M-81531 & SAE-DTL 23053/5 (Class 1 & 3) - RoHS compliant  			BLACK ON WHITE	18051	18053	18055	18057	–
			BLACK ON YELLOW	18052	18054	18056	18058	–
<b>FLEXIBLE NYLON</b>  Length 11.5'   3.5 m  - UL Recognized Component to UL969 - RoHS compliant  			BLACK ON WHITE	–	–	18488	18489	1734524
			BLACK ON YELLOW	–	–	18490	18491	1734525
<b>NON-ADHESIVE TAG</b>  Length 18'   5.5 m  - RoHS compliant  			BLACK ON WHITE	18111	–	18113	–	–
<b>SELF-LAMINATING</b>  Length 18'   5.5 m  - RoHS compliant  			BLACK ON WHITE	–	–	–	–	1734821

Distributed by:

**Accu-Tech®**  
We're Known by the Companies We Keep

For more information, please visit:  
[www.accu-tech.com](http://www.accu-tech.com)



A **NewellRubbermaid** Brand