

Product Cut Sheet

STANDARD SWING GATE RACK

The Standard Swing Gate Wall Rack provides easy access to the rear of equipment, making it the ideal choice for supporting patch panels and switches.




- Dual hinges opens to right or left, stopping in 90° position
- EIA-310-D compliant
- Universal 5/8"-5/8"-1/2" (15.9 mm -15.9 mm -12.7 mm) alternating hole pattern
- RMU spaces are marked
- Supports 100 lb (45.4 kg) of equipment in the open and closed position when securely mounted
- Load capacity can be increased to 150 lb with optional Heavy Duty Swing Gate Kit
- Supports single-sided and double-side shelves
- Ships partially assembled with installation hardware
- Includes (50) #12-24 mounting screws; black painted units ship with black screws, clear units ship with zinc screws
- UL Listed



Usable Depth:

12" (300 mm) = 11" (280 mm) usable
18" (460 mm) = 17" (430 mm) usable
25" (640 mm) = 24" (610 mm) usable



Part Number	Height	RMU	Depth	Shipping Weight
19" Wide Rack				
11790-X12	24.5" (622 mm)	13	12" (300 mm)	22 lb (10.0 kg)
11790-X18	24.5" (622 mm)	13	18" (460 mm)	24 lb (10.9 kg)
11790-X25*	24.5" (622 mm)	13	25" (640 mm)	42 lb (19.1 kg)
11791-X12	38.5" (978 mm)	21	12" (300 mm)	24 lb (10.9 kg)
11791-X18	38.5" (978 mm)	21	18" (460 mm)	26 lb (11.8 kg)
11791-X25*	38.5" (978 mm)	21	25" (640 mm)	46 lb (20.9 kg)
11807-X12	49.0" (1245 mm)	27	12" (300 mm)	25 lb (11.3 kg)
11807-X18	49.0" (1245 mm)	27	18" (460 mm)	26 lb (11.8 kg)
11807-X25*	49.0" (1245 mm)	27	25" (640 mm)	50 lb (22.7 kg)
11792-X12	73.5" (1867 mm)	41	12" (300 mm)	31 lb (14.1 kg)
11792-X18	73.5" (1867 mm)	41	18" (460 mm)	33 lb (15.0 kg)
11792-X25*	73.5" (1867 mm)	41	25" (640 mm)	60 lb (27.2 kg)
23" Wide Rack				
11793-X12	24.5" (622 mm)	13	12" (300 mm)	23 lb (10.4 kg)
11793-X18	24.5" (622 mm)	13	18" (460 mm)	25 lb (11.3 kg)
11793-X25*	24.5" (622 mm)	13	25" (640 mm)	43 lb (19.5 kg)
11794-X12	38.5" (978 mm)	21	12" (300 mm)	25 lb (11.3 kg)
11794-X18	38.5" (978 mm)	21	18" (460 mm)	27 lb (12.2 kg)
11794-X25*	38.5" (978 mm)	21	25" (640 mm)	47 lb (21.3 kg)
11808-X12	49.0" (1245 mm)	27	12" (300 mm)	26 lb (11.8 kg)
11808-X18	49.0" (1245 mm)	27	18" (460 mm)	28 lb (12.7 kg)
11808-X25*	49.0" (1245 mm)	27	25" (640 mm)	51 lb (23.1 kg)
11795-X12	73.5" (1867 mm)	41	12" (300 mm)	32 lb (14.5 kg)
11795-X18	73.5" (1867 mm)	41	18" (460 mm)	34 lb (15.4 kg)
11795-X25*	73.5" (1867 mm)	41	25" (640 mm)	61 lb (27.7 kg)

X=Color: 1=Gray, 2=White, 5=Clear 7=Black

*-X25 not available in clear

Heavy Duty Swing Gate Kit

Increases the load bearing capacity of the 18"D (460 mm) and 25"D (640 mm) model Standard Swing Gate Wall Racks up to 150 lb (68 kg). Includes installation hardware and instructions.

Part Number	Description	Shipping Weight
12795-X01	Two Brackets	4 lb (1.8 kg)

X=Color: 1=Gray, 2=White, 7=Black



800-834-4969 in U.S. & Canada • www.chatsworth.com



CHATSWORTH PRODUCTS, INC.

©2010 Chatsworth Products, Inc. All rights reserved. CPI, CPI Passive Cooling, MegaFrame, Saf-T-Grip, Seismic Frame, SlimFrame, TeraFrame, Cube-IT Plus, Evolution, OnTrac, and QuadraRack are federally registered trademarks of Chatsworth Products, Inc. GlobalFrame, Simply Efficient and Velocity are trademarks of Chatsworth Products, Inc. All other trademarks belong to their respective companies. 12/10