

# Product Specifications

## 360DM-12LC-LS

Material ID: 760109926

InstaPATCH® 360 360DM-12LC-LS Module



## CHARACTERISTICS

### Construction Materials

Fiber Type	LazrSPEED® 550, 50 µm multimode fiber
Total Fibers, quantity	12

### Dimensions

Depth	116.8 mm   4.6 in
Height	30.48 mm   1.20 in
Width	91.4 mm   3.6 in

### Environmental Specifications

Safety Standard	UL
-----------------	----

### General Specifications

Interface, front	LC
Total Ports, quantity, front	12
Interface Feature, front	Standard
Color, front	Aqua
Brand	InstaPATCH® 360
Interface, rear	MPO
Adapters, quantity, rear	1
Interface Feature, rear	Reduced footprint
Color, rear	Gray
Package, quantity	1

### Optical Performance

Insertion Loss Change, mating	0.30 dB
Insertion Loss Change, temperature	0.30 dB
Insertion Loss, maximum	0.50 dB

# Product Specifications

360DM-12LC-LS - Material ID: 760109926

Return Loss, minimum 20.0 dB

## Regulatory Compliance/Certifications

---

### Agency

RoHS 2002/95/EC  
ISO 9001:2008

### Classification

Compliant  
Designed, manufactured and/or distributed under this quality management system



## \* Footnotes

---

Insertion Loss Change, mating Maximum insertion loss change after 500 matings

Insertion Loss Change, temperature Maximum insertion loss change from 0 °C to +60 °C (+32 °F to +140 °F)