

High quality color CRT monitors with multiple inputs, built-in speaker and on-screen-display



DESCRIPTION

Infinova's V1321T-14 series 14" CRT color monitor has 430 lines of resolution. It features two channels of video and one channel audio, stackable case, with built-in speaker and OSD.

Infinova's V1322T-21 series 21" CRT color monitor has 500 lines of resolution. It features three channels of both video and audio. It is the perfect match for displaying high-resolution video and includes a stackable case, with built-in speaker and OSD.

Infinova's V1324T-17 series 17" flat CRT color monitor has 800 lines of resolution. It features three channels of both video and audio. This high-resolution monitor provides exceptional performance for demanding security applications and includes a stackable case, with built-in speaker and OSD.

FEATURES

V1321T-14

- 14" High quality CRT color monitor with built-in speaker
- Resolution: 430 TVL
- Two Channels Video with One Audio. Manual Switching.
- 1 S-video input/output, 1 BNC video input/output, 1 RCA audio input/output. Auto Termination. Rear panel selectable.
- NTSC/PAL system auto switch
- Multi-Language OSD (On Screen Display)
- Stackable Case, Universal Power 100~240 VAC, 50Hz/60Hz

V1322T-21

- 21" High-resolution CRT color monitor with built-in speaker
- Resolution: 500 TVL
- Three Channels Video with Audio. Manual / Auto Switching.
- 1 S-video input/output, 2 BNC input/output, 3 RCA audio input/output. Auto Termination. Front panel selectable.
- NTSC/PAL system auto switch
- Multi-Language OSD (On Screen Display)
- Stackable Case, Universal Power 100~240 VAC, 50Hz/60Hz

V1324T-17

- 17" High-resolution flat CRT color monitor with built-in speaker
- Resolution: 800 TVL
- Three Channels Video with Audio. Manual Switching.
- 1 S-video input/output, 2 BNC input/output, 3 RCA audio input/output. Auto Termination. Front panel selectable.
- NTSC/PAL system auto switch.
- Multi-Language OSD (On Screen Display).
- Stackable Case, Universal Power 100~240 VAC, 50Hz/60Hz.

ORDERING INFORMATION

V1321T-14	CRT Monitor, 14", 430TVL, Color, NTSC/PAL, 1 S-video input/output, 1 BNC input/output, 1 RCA audio input/output
V1322T-21	CRT Monitor, 21", 500TVL, Color, NTSC/PAL, 1 S-video input/output, 2 BNC input/output, 3 RCA audio input/output
V1324T-17	CRT Monitor, 17", 800TVL, Color, NTSC/PAL, 1 S-video input/output, 2 BNC input/output, 3 RCA audio input/output

SPECIFICATIONS

Diagonal CRT Size:	
V1321T-14:	14"
V1322T-21:	21"
V1324T-17:	17"
Video Input/Output:	
V1321T-14:	1 ch. BNC video input/output, 1 S-video input/output
V1322T-21:	2 ch. BNC video input/output, 1 S-video input/output
V1324T-17:	2 ch. BNC video input/output, 1 S-video input/output
Audio Input/Output:	
V1321T-14:	1 ch. RCA audio input/output
V1322T-21:	3 ch. RCA audio input/output
V1324T-17:	3 ch. RCA audio input/output
Resolution:	
V1321T-14:	430 TVL
V1322T-21:	500 TVL
V1324T-17:	800 TVL
Panel Control:	Menu, channel, power
Input Voltage:	Universal 100~240VAC, 50Hz/60Hz
Power Consumption:	
V1321T-14:	65 W (Max.)
V1322T-21:	80 W (Max.)
V1324T-17:	100 W (Max.)

SPECIFICATIONS (Continued)

Temperature:	14°F ~ 122°F (-10°C ~ 50°C)
Humidity:	10~90% RH (non-condensing)
Dimensions (WxHxD)	
V1321T-14:	13.8"×13.8"×14.2" (350 mm×350 mm×360 mm)
V1322T-21:	19.4"×18.7"×19.0" (492 mm×474 mm×482 mm)
V1324T-17:	16.4"×15.7"×16.4" (416 mm×400 mm×417 mm)
Weight:	
V1321T-14:	30.87 lbs. (14 kg)
V1322T-21:	59.53 lbs. (27 kg)
V1324T-17:	44.10 lbs. (20 kg)

Compliance: FCC, CE
ISO 9001:2000