

MAXCELL® PREMISE

MaxCell Premise meets the most stringent inside plant requirements, making it the ideal solution for new cable installation in indoor conduit applications. This single solution is designed for plenum and riser applications in cable routing assemblies and communication raceways. It's UL listed and low smoke zero halogen compliant for in-building enterprise applications, data centers, and confined builds where space and safety are a priority.

Features and Benefits

- UL 2024 - OFCR FT-6 Listed
- Low smoke zero halogen compliant; plenum and riser compliant
- White fabric color is easy to identify
- Color differentiated pull tapes are pre-installed within each cell
- Designed for use in ducts ranging from 1.25" - 4" (I.D.)
- Configured in 1 to 3-cell packs
- Manufactured in the U.S.A.



PLENUM

Product Number	Description	Max Cable (O.D.) Capacity Per Cell	Max # of Packs Per Conduit Size					
			1.25"	2"	3"	4"	5"	6"
MXP4003BK####	4" 3-Cell Plenum, 1250# Tape	38mm / 1.5"				2	3	4
MXP3456BK####	3" 3-Cell Plenum, 1250# Tape	28mm / 1.05"			2	3	4	5
MXP2003BK####	2" 3-Cell Plenum, 1250# Rope	22mm / 0.85"		1				
MXP2002BK####	2" 2-Cell Plenum, 1250# Rope	22mm / 0.85"		1				
MXP2001BK####	2" 1-Cell Plenum, 1250# Rope	22mm / 0.85"		1				
MXPM3303BK####	1.25" 3-Cell Plenum, 1250# Rope	12mm / 0.45"	1					
MXPM3302BK####	1.25" 2-Cell Plenum, 1250# Rope	12mm / 0.45"	1					
MXPM3301BK####	1.25" 1-Cell Plenum, 1250# Rope	12mm / 0.45"	1					

Important Installation Tips

- Swivels must be used when pulling Premise products
- The factory installed pull tapes in each cell must free-float during installation
- Contact customer service for installation assistance

Design and fabrication of MaxCell is patent protected.

